
Infrared Spectromicroscopy (FTIRSM) • Beamline 1.4.3

Berkeley Lab • University of California

Beamline Specifications

<u>-</u>			
Photon Energy Range (cm ⁻¹)	Spectral Resolution (cm ⁻¹)	Spot Size (µm)	Availability
450–10,000 (0.05–1 eV)	0.125	<10 (diffraction limited)	NOW



Schematic layout of Beamline 1.4.3.

eamline 1.4 serves three distinct experimental stations designated as Beamlines 1.4.1, 1.4.2, and 1.4.3. Beamline 1.4.3 provides state-of-the-art Fourier transform infrared (FTIR) spectromicroscopy in the mid-IR region from 10,000 to 450 cm⁻¹. All-reflecting optics focus the bendmagnet radiation into a switchyard. The switchyard houses optics that collimate the radiation and distribute it to the three experimental stations.

The synchrotron beam serves as an external source for a Nicolet Magna 760 FTIR bench. The beam, after being modulated by the moving mirror in the Michaelson interferometer in the 760, passes


into a Nicolet Nic-Plan IR microscope. The Nic-Plan has two all-reflecting objectives, 15× and 32×, which allow both reflecting and transmitting modes of operation. A grazing-incidence objective and a variable-temperature stage (70–730 K) are available. A computer-controlled, motorized sample stage can obtain spectral maps with 1-μm spatial precision.

Since the synchrotron beam is many times brighter than conventional IR sources, the beam may be focused to small diameters with little loss of signal. With the $32\times$ objective, the full-width, half-maximum (FWHM) spot size, integrated over all mid-IR wavelengths, is less than $10~\mu m$. This spot

size becomes diffraction limited at longer wavelengths. When measuring areas with diameters less than $100~\mu m$, the synchrotron provides substantial improvement in signal over the conventional globar source.

Typical experiments are in environmental science (adsorbates, bacteria, soil chemistry, remediation), particulate contamination (defects on silicon

wafers), biological materials (bioremediation, identification of biomolecules, tissue analysis), microscopic films and crystals (novel electronic materials and molecules), polymer laminates and composites (photographic film), forensic studies (drug identification, fiber analysis), and systems at high pressure (materials in diamond anvil cells). Visit infrared.als.lbl.gov for more information.



Spatially resolved, time-dependent evidence for biogeochemical transformation of hexavalent chromium (Cr⁶⁺), a widespread industrial contaminant. After a four-month exposure of basalt rock chips to solutions of Cr⁶⁺ and toluene vapor, FTIR spectromicroscopy showed that Cr⁶⁺-tolerant and Cr⁶⁺-reducing microorganisms were thriving in association with Cr³⁺. Data courtesy of Hoi-Ying Holman, Dale L. Perry, Michael C. Martin, Wayne R. McKinney (Berkeley Lab), and Jennie C. Hunter-Cevera (University of Maryland).

This beamline is available to independent investigators by submitting a proposal.

For Beamline Information

Michael C. Martin Advanced Light Source Berkeley Lab, MS 7-222 Berkeley, CA 94720 Phone: (510) 495-2231 Fax (510) 486-7696 Email: mcmartin@lbl.gov

PRT Spokesperson

Wayne R. McKinney Advanced Light Source Berkeley Lab, MS 2-400 Berkeley, CA 94720 Phone: (510) 486-4395 Fax: (510) 486-7696 Email: wrmckinney@lbl.gov

To Obtain a Proposal Form

Bernie Dixon User Services Office Manager Advanced Light Source Berkeley Lab, MS 6-2100 Berkeley, CA 94720 Tel: (510) 486-6722 Fax: (510) 486-4773 Email: alsuser@lbl.gov

